



ULTRA PORTABLE DLP[®] PROJECTOR – DX650

FEATURE AND BENEFIT

1. DLP™ TECHNOLOGY, SUPERIOR PICTURE QUALITY
2. NATIVE 1024x768, COMPATIBLE UP TO 1280x1024
3. 1600ANSI AND 600:1 HIGH CONTRAST, SUPERIOR BRIGHTNESS AND CRISP COLOR CLARITY
4. ONLY 6.8 LBS, LIGHTWEIGHT FOR ANY APPLICATION
5. DIGITAL KEYSTONE –
EASIER TO PROJECT AT DIFFERENT ANGLES
6. HDTV COMPATIBLE (720P, 1080i, 480P)
7. PICTURE IN PICTURE (SEE VIDEO IN COMPUTER PICTURE)
8. MANUAL ZOOM LENS, EASIER PROJECTION AT ANY DISTANCE
9. 10 X DIGITAL ZOOM - ZOOM AND PAN FOR SMALL TEXT
10. AUTO KEY, PLUG AND PROJECT
11. FULL FUNCTION INTELLIGENT REMOTE CONTROL WITH BUILT-IN LASER POINTER AND WIRELESS MOUSE TO CONTROL YOUR PC FROM ANYWHERE
12. BUILT-IN RS232 CONTROL PORT FOR ANY CONTROL SYSTEM
13. WIDE ANGLE LENS, 25% LARGE SCREEN THEN STANDARD PROJECTOR IN SAME PROJECT DISTANCE
14. FREE CARRYING BAG FOR STORAGE OR TRAVELING
15. IBM PC AND MAC COMPATIBLE
16. DIRECT Y Pb Pr INPUT – EASY FOR P-SCAN DVD PLAYER



| | |
|------------------------------------|--|
| Model Name | DX650 |
| Projection System | DLP™ |
| Panel | 0.7" DMD™ x 1 |
| Native Resolution | 1024x768 (XGA) |
| Resolution Supported | 640 x 350 to 1280 x 1024 (SXGA) |
| Brightness | 1600 ANSI Lumens |
| Image Size | 22" to 300" |
| Throw Ratio | 600" @ 6.6 feet |
| Zoom Ratio | 1:1.2 |
| Projection Distance | 2.6' to 32.8' |
| Lens | Manual Zoom, F=2.6 to 3.1, f=23-27.6 mm |
| Uniformity | 85% |
| Contrast Ratio | 600:1 |
| Color | Full 16.7 million color palette |
| Aspect Ratio | 4:3/16:9 screen selectable |
| Horizontal Frequency | 20~88 kHz |
| Vertical Scan Rate | 20~100 Hz |
| Projection Position | Front / Rear, Table / Ceiling |
| Lamp | 210 W NSH, 2000 hours lamp life |
| Audio Noise | <34db |
| Input Terminals | RGB: Analog-D-sub 15 pin x 1 (PC or MAC) S-Video: Mini DIN 4 pin x 1 Composite Video and Audio: RCA(L/R) x 2 Component (Y Pb Pr), RCA jack x 3 Audio: Stereo Mini Jack x1 -PC Mouse Control Port: USB x 1 RS232 Control port x 1 |
| Output Terminals | RGB: Analog D-sub 15 pin x 1 3W Speaker x 1 |
| Video Compatible | NTSC / PAL / SECAM / NTSC 4.43 |
| Body Material | Magnesium Alloy |
| Body Color | Silver |
| Dimensions | 12.13 x 3.74 x 9.45 (W x H x D) |
| Weight | 6.8lbs |
| Power Supply | 100 to 240 VAC, 50 to 60 Hz |
| Power Consumption | 330W (Max.) |
| On-Screen Display Languages | English/French/German/Italian/Spanish /Traditional Chinese/Simplified Chinese/Korean |
| Functions | Digital Keystone Auto HDTV Compatible P-Scan/Video Mode Freeze / Blank / Volume Digital Zoom / Source Detection Picture in Picture Laser Pointer / Wireless Mouse |
| Accessories (Standard) | User's Guide / User's CD Manual Remote Control / AAA Batteries Power cord (UK, US, Pan-Europe) 3-2 converter Soft Carry Bag 15 pin D-sub VGA connector PC-PC Audio cable RCA jack (Audio / Video) USB cable S-Video cable |