



EPSON PowerLite® 735c

Wireless Presentation at its Best

The industry's lightest wireless presentation solution to date, the 4.4 lb EPSON PowerLite® 735c offers remarkable control flexibility with 802.11b wireless technology. Designed to facilitate quick setups and easy network management, this 2000 ANSI lumen, ultra portable projector also offers remote diagnostics and monitoring.

In addition, its newly improved EasyMP $^{\sim}$ technology enables convenient PC-free presentations with incredible PowerPoint $^{\circ}$ functionality and brilliant high-speed transitions.

With EPSON 3-LCD technology and XGA resolution, this full-featured performer delivers exceptional image quality in any situation.

Newly improved EPSON EasyMP

- PC-free presenting
- More animation and PowerPoint functionality than ever before
- · High-speed image transfers

Convenient connectivity options, including wireless capability!

- No video cable required Laptop and projector can be positioned independently for optimal viewing and control.
- 802.11b wireless technology (WiFi™ certified)
- · Two wireless modes for individual or LAN users
- · Easy administration via web browser access
- Simple Network Management Protocol (SNMP) for easy network management and maintenance
- Control flexibility displays images on up to four projectors simultaneously
- Security features safeguards the display screen for uninterrupted presentations

Incredible brightness-to-weight ratio!

- · 2000 brilliant ANSI lumens
- · Weighs just 4.4 lb

Superior image quality

- Three 0.9" high-aperture EPSON LCDs with Micro Lens Array, for rich color saturation across the screen
- XGA (1024 x 768) resolution for sharp, vivid detail
- 400:1 contrast ratio for blacker blacks and whiter whites


Easy setup and operation

- · Easy-to-use remote control that's stored within the projector
- · Exclusive auto keystone correction
- · Color-coded VGA cables and connectors
- HDTV-ready
- · Optical zoom
- Start Here Kit gets first time users projecting in just minutes

Renowned EPSON service and support (free for the duration of the warranty)

- Comprehensive two-year warranty
- · 90-day bulb warranty for added dependability
- EPSON Road Service Program provides a replacement projector, typically within 24 hours
- EPSON PrivateLineSM dedicated toll-free support line available from 6 a.m. to 6 p.m. PST Monday - Friday (Calls are answered live, typically in about a minute.)
- · International warranty in over 45 countries





EPSON PowerLite 735c Specifications

| Projection System | EPSON original LCD prism technology | | | |
|--|---|--|---|------------------------|
| Projection Method | Front/rear/ceiling mount | Card I/O PC card slot | PCMCIA type I/II | |
| LCD | | Memory card | Compact Flash, Smart I | Media, Memory Stick, |
| Size | 0.9" | compatibility | SD, MMC, 3.3 volts typ | e ATA Flash card, |
| Driving Method | EPSON Poly-Silicon TFT Active Matrix | | 5 volts type ATA Flash of | card, IBM MicroDrive™ |
| Pixel Number Native Resolution | 786,432 dots x3 (1024 x 768) LCDs XGA | 011 | MC - L L ANI L / L | 11 |
| Aspect Ratio | 4:3 (supports 16:9, 5:4) | Other | Wireless LAN card (star Wired LAN card | idard accessory only) |
| Pixel Arrangement | Stripe | | Wiled LAN Cald | |
| Projection Lens | | Video I/O Display performance | 550 TV Line | |
| Type | Manual: zoom/focus | Display performance | 550 TV LINE | |
| F-number | 1.9 to 2.1 | Input signal | NTSC/NTSC4.43/PAL/M | -PAL/ |
| f-number | 31 – 36mm | , , , , | N-PAL/PAL60/SECAM | |
| Zoom ratio | 1:1.16 | Input terminal | | |
| Lamp | | Video | HDTV: 480i, 480p, 720 | · · |
| Type | 150W UHE | | Composite Video: RCA S-Video: Mini DIN | ΧI |
| Life (typical) | 1500H (can last about 5 yrs. based on 6 hours/week x 50 weeks/year) | | Component Video: Mir | ni D-sub 15pin |
| | | | (in common with Analo | |
| Screen Width Ratio: (dist | ance/width) 1.63 to 1.89:1 | | Video RGB: Mini D-sub | 15pin |
| Screen Size (projected distance) 30" to 300" (1.0m to 11.7m) | | A 11 | (in common with Analo | g RGB connector) |
| Keystone Correction | +/- 15 degrees | Audio | Stereo mini jack | og PCP audio iack) |
| Brightness (typical) | 2000 ANSI lumens | | (in common with Analo | ng kgb audio jack) |
| Contrast Ratio | 400:1 | Audio signal | 500m Vrms/47Kohm | |
| Brightness Uniformity (ty | | Control I/O | | |
| | ,, , | I/O terminal | USB type B x 1 (for mo | use, keyboard control |
| Color Reproduction | 24 bit; 16.7ml | | and RS-232 communica | . , |
| Sound Output | 1W | Security | Kensington®-style lock | provision |
| Operating Temperature | 5°C to 35°C (41°F to 95°F) | Warranty | | |
| Power Supply Voltage | 100-120V, 200-240V +/-10%, 50/60Hz AC | | ed warranty, 2-year internatio | |
| Power Consumption | 225W / 35W at sleep mode: Network On 5.5W at sleep mode: Network Off | | Road Service Program and EPS ort (U.S. and Canada only) | ON PrivateLine |
| NA. 1 | <u>'</u> | Supplied Accessories | ort (0.5. and oandad orny) | |
| Maximum Dimensions D (includes lens and feet) | 7.5" x 10.9" x 3.1" | | remote control with lithium ba | attery computer cable |
| (excludes lens and feet) | 7.5" x 10.9" x 2.7" | | cable, USB mouse cable, Wir | |
| Weight | 4.4 lbs/1.9kg | Here Kit, CD-Rom, soft | carrying case | |
| Fan Noise | 39db | Product/Accessory Pa | | |
| | | EPSON PowerLite 735c | Projector | V11H103020 |
| Effective Scanning Frequency Pixel Clock | 13.5MHz to 162MHz | Replacement lamp | case (16.75" x 15" x 9") | V13H010L18 ELPKS24 |
| Horizontal | 15KHz to 92KHz | Soft shoulder bag | (10.70 × 10 × 7) | ELPKS31 |
| Vertical | 50Hz to 85Hz | Notebook/projector soft | shoulder bag | ELPKS32 |
| Remote Control | | | notebook/projector case | ELPKS42 |
| Features | Keystone, special effects, source selection, | Ceiling mount | | ELPMB37 |
| | power, color mode, page up/down, | Suspension adapter | | ELPMBAPL |
| | volume, presets | False ceiling plate | | ELPMBFCF |
| | | Distribution amplifier Component video cable | | ELPDA01 ELPKC19 |
| Operating Angle | +/_ 30° horizontally | S-video cable | | ELPSV01 |
| | ⁺ /_ 15° vertically | Mac adapter set | | ELPAP01 |
| Operating Distance | 20ft (6m) | 50" portable project | ion screen | ELPSC06 |
| | 20.1 (011) | 60" portable pop-up | | ELPSC07 |
| RGB | Analog RGB I/O | 80" portable pop-up | | ELPSC08 |
| Display performance | , and sign to be to | High resolution docume High resolution docume | 9 | ELPDC02 V12H064020 |
| Native | 1024 x 768 | Kensington security lock | | V 12H06402C ELPSL01 |
| Resize | 1600 x 1200 | | | LLI JLO I |
| | 1280 x 1024 | Support-The Epson C | | 800-463-7766 |
| | 800 x 600 | | Pre-Sales Support U.S. and Canada 800-463-77 Automated Technical Support 800-922-89 | |
| | 640 x 480 | THE STATE OF THE S | • • | www.epson.com |
| | | | | |
| Input terminal | | Presenters ONLINE | • | nresentersonline com |
| Input terminal Video Audio | Mini D-sub 15pin x 1 Stereo mini jack | Presenters ONLINE | • | presentersonline.com |



Epson America, Inc.

3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.

3771 Victoria Park Ave, Toronto, Ontario M1W 3Z5

Epson Latin America

6303 Blue Lagoon Drive, Miami, FL 33126

Specifications and terms are subject to change without notice. EPSON is a registered trademark and EasyManagement is a trademark of Seiko Epson Corporation. PowerLite is a registered trademark, SizeWise is a trademark and Epson Connection, PrivateLine and Presenters Online are service marks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. © Copyright 2003 Epson America, Inc. CPD-15540 25K 2/03 CL Printed on Recycled Paper