

# HITACHI

Inspire the Next

# CP-X885W



- 3,500 ANSI Lumens
- Native XGA resolution
- Full Connectivity
- Contrast Ratio 800:1
- Power zoom 1:1.5/ power focus
- Vertical & horizontal keystone correction
- Auto Keystone correction
- My screen (user-programmable start-up and blank screen)
- Easy lamp replacement

#### Forget-Me-Not Features

- Reverse image function
- 35dB (Whisper mode)
- Picture-in-picture
- Color temperature and gamma correction
- Digital zoom and freeze function

## SPECIFICATIONS

<b>Model name</b>	CP-X885W			
<b>Liquid crystal panel structure</b>	0.99" polysilicon active-matrix TFT x 3			
<b>Number of pixels</b>	786,432 pixels (H1,024 x V768)			
<b>Native resolution</b>	1,024 x 768 color pixels			
<b>Colors</b>	16.7 million colors			
<b>Aspect ratio</b>	Native 4:3 (16:9 resizing mode)			
<b>Lens</b>	Power Zoom (F=1.7-2.4) 1:1.5 (F=30.5-45.8) Power focus			
<b>Throw ratio (distance:width)</b>	1.5 ~ 2.26:1			
<b>Lamp</b>	275W UHB			
<b>Expected lamp life</b>	2,000 hours (approx)			
<b>Brightness</b>	3,500 ANSI Lumens (approx. 2,800lm in whisper mode)			
<b>Contrast ratio</b>	800:1			
<b>Speakers</b>	1W x 2			
<b>Power supply</b>	AC100-120V/AC220-240V			
<b>Power consumption</b>	430W			
<b>Operating temperature</b>	0-35°C (31-95°F)			
<b>Input signals</b>	RGB	VGA, SVGA, XGA SXGA (compressed), UXGA (compressed), MAC13", MAC16", MAC19"		
	Composite video	NTSC, NTSC4.43, PAL, PAL60, N-PAL, M-PAL, SECAM		
	Component video	480i, 575i, 480p, 1,080i, 720p		
<b>Noise level</b>	39dB (35dB in whisper mode)			
<b>H Sync</b>	15kHz - 91kHz			
<b>V Sync</b>	50Hz - 120Hz			
<b>Vertical keystone correction</b>	Digital keystone +/- 15°			
<b>Horizontal keystone correction</b>	Digital keystone +/- 5°			
<b>Other features</b>	Picture freeze, Digital zoom, User programmable start-up screen, Picture-in-picture, Gamma correction, Image reverse function, Auto-sync/auto-keystone button			
<b>Input/Output terminals</b>	RGB input	Analog RGB	15-pin D-sub x 1 BNC x 5 (shared with video)	
		Digital RGB	DVI-D x 1	
	Video input	Audio	Stereo mini jack x 2	
		S-video	Mini DIN 4-pin x 1	
		Composite	RCA jack x 1	
	RGB output	Component	RCA jack x 3 BNC x 3 (shared with RGB)	
Audio		RCA jack x 2 (L/R)		
<b>Chassis</b>	RGB output	Analog RGB	15-pin D-sub x 1	
		Audio	Stereo mini jack x 1	
	Control terminals	D-sub, 15-pin x 1		
	Remote mouse terminal	USB x 1, D-sub 15-pin x 1		
	Dimensions	14.94" x 4.75" x 11.44" (W x H x D)		
	Weight	12 lbs. 9oz		
<b>Spare/option accessories</b>	Approvals	UL, C-UL, FCC class-B, CE, TUV		
	Supplied accessories	Wireless remote control with mouse and laser pointer, AA batteries, Power cord, RGB-cable, Video-cable (composite), USB-cable, Operators manual, Soft carry case		
	Lamp model name	CP885/880 LAMP (Part # DT00531)		
	Spare remote control	HL01771		
	Optional wireless module (LAN/wireless data transfer)	WNM80		



Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
30	24	34	52
40	32	46	71
50	40	58	89
60	48	71	107
70	56	83	126
80	64	95	144
90	72	108	162
100	80	120	181
120	96	144	217
150	120	181	272
200	160	243	364
250	200	304	455
300	240	366	547

Throw ratio: 1.5 ~ 2.26:1 (distance:width)

\*: Measured in inches



**CP-X880/CP-X885 Dimensions** (incl.protruding part)

