## ASK Proxima C110 Projector Technical and Functional Specifications

## General

Aspect Ratio: 4:3, 16:9

Brightness: 1600 max ANSI lumens; 1100 max in whisper mode

Contrast Ratio: 2000:1 full on/full off

Data Compatibility: VGA, SVGA, XGA (PC and Mac)

Display: DLP by Texas Instruments: 0.55" SVGA DDR DMD

Image Size (diagonal):2.7 to 21.6 feet (.8m to 6.6m)Projection Distance:5 to 32.3 feet / 1.5 - 9.8mThrow ratio:1.89 - 2.27 (distance/width)Light Source:200W SHP / 3,000 hoursNative Posclution:SVGA (800x600)

Native Resolution: SVGA (800x600)

Projection Methods: Front, rear, and ceiling
Digital Keystone +/- 10 degrees (vertical)

Correction:

Video Compatibility: SDTV: NTSC, PAL, SECAM

EDTV: 480p, 576p HDTV: 1080i and 720p

H-Sync Range: 31.5 - 80 kHz

V-Sync Range: 50 – 85 Hz (85Hz at XGA only)

Size

Dimensions: 9.8" (W) x 12.9" (L) x 4.2" (H) / 24.9cm x 32.7cm x 10.5cm

Weight: 6.8 lbs / 3.1kg

Input

Control: Projector keypad, IR remote control
Input Sources: 1 - M1-DA (computer and video sources)
1 - S-Video 4-pin mini DIN (S-Video)

1 - Composite (Video)

2 - Audio (stereo RCA for computer and video)

Output

Audio: 2.5 Watt mono speaker

Number of Colors: 16.7 million

Audible Noise: 39dB (standard mode); 37dB (whisper mode)

Outputs: Audio mini-jack, monitor loop through, 12V trigger for electric screens

Other

Lamp Warranty: 90 days or 500 hours, whichever comes first Operating Temperature: 5° – 40° C at sea level (0′ –10,000′); 41° – 104° F

Power Consumption: 200 Watt (typical); 250 Watt (maximum)
Power Supply: 100 – 240V at 50 – 60 Hz, auto switching
Ships Standard with: • User Manual, quick-start guide, CD

Soft carrying case

· Lens cap

• Navigator Remote Control (batteries included)

M1 to VGA/USB-A cableComposite video cable

Menu Languages: English, Spanish, French, German, Japanese, Korean, Portuguese, Italian, Norwegian, Russian,

Simplified Chinese, Traditional Chinese

Approvals: UL, c-UL, TUV GS, CE, GOST, C-Tick, NOM, IRAM, FCC B, CISPR22 /EN55022, EN 55024 /

CISPR 24, CB certified according to IEC60950 /EN60950: 1997, P(SE), MIC

Projector Warranty: 1 year parts and labor

Accessory Warranty: 1 year

Lamp Warranty: 90 days / 500 hours, whichever comes first

Copyright © 1997-2004 InFocus Corporation. All Rights Reserved.