C180

Full performance, excellent image quality.



ProjectorNet





Full Color, Full Image

Outstanding color saturation plus best-in-class performance equals a presentation that will be remembered. If it's brightness that opens your eyes, a long-life UHP lamp lets your message shine 2200 lumens strong. This projector combines breakthrough features like automatic vertical keystone adjustment and even goes a step further than most with horizontal keystone correction and automatic image synchronization with your computer.

Full Functionality

Experience low maintenance and easy installation with the ASK Proxima C180. Take advantage of out-of-the-box networking with InFocus® ProjectorNet™ software and control your projectors from a central location. With the InFocus LiteShow® wireless solution, you can take advantage of wireless freedom in any meeting room to project instantly, without any cable hassle.

Fully Intuitive

The ASK Proxima C180 was designed by a breakthrough engineer; you. Years of intensive user research have enabled high-end innovations to be as easy to use as operating a telephone. Automatic keystone correction and ceiling detection ensure your image is set up correctly, with no manual work on your part. Automatic synchronization with computer and video sources allow for quick starts and smooth transitions.

Ease, Incorporated

Imagine. A projector that works the way you do. Thoughtful innovations make projecting easier than it's ever been before—from setup, use, options and management. It's one-touch, instant projection, with unparalleled ease-of-use that lets you present without hassles or practice. It's a design philosophy from InFocus Corporation called ProjectAbilityTM and it's incorporated into every ASK Proxima projector for your guaranteed success.



Easy to use, easy to support and easy to share.



A 12-language interactive display offers status information in real time. The user friendly keypad lets you control most commands with the touch of a button.

ASK Proxima



TECHNICAL SPECIFICATIONS

TECHNICAL SPEC	FIFICATIONS
Native Resolution	• XGA 1024 x 768
Display Technology	• 3 x .79" polysilicon TFT LCD, active-matrix
Computer Input	 Computer 1 (M1-DA), Computer 2 (VESA),
Sources	Audio (3.5mm Stereo)
Wireless Connectivity	Yes with optional LiteShow®
Networking	 Yes with optional ProjectorNet™software
Video Input Sources	 Video 1 (S-Video), Video 2 (Composite RCA),
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Audio (RCA Stereo)
Control Input Sources	• RS232, USB
Output Sources	Variable Stereo Audio (RCA), Monitor Out (VESA)
Computer Compatibility	 SXGA+, SXGA, XGA, SVGA, VGA, Macintosh®, HDTV 1080i, 1080p, 720p, 480p, 576p
Video Compatibility	 Full NTSC, PAL, SECAM, HDTV 1080i, 1080p, 720p, 480p
Brightness	2200 max ANSI lumens
Brightness Uniformity	• 75%
Contrast Ratio	• 400:1
Number of Colors	• 16.7 million
H-Synch Range	• 16 – 110 kHz
V-Synch Range	• 50 – 85 Hz
Dot Clock	• 135 MHz
Automatic Ceiling	
Detection	• Yes
Automatic Vertical	
Keystone Correction	• Yes
Digital Keystone	
Correction (Horizontal)	+/- 15°; data/video
Digital Keystone	
Correction (Vertical)	+/- 25°; data/video
Projection Lens	Zoom lens with manual focus and manual zoom adjust
Zoom Ratio	• 1.2:1
Throw Ratio	• 1.6:1 – 1.9:1 (D:W)
Projection Distance	• 5' – 32.8' (1.5m - 10.0m)
Image Offset ratio (%)	• 95 ± 5 %
Aspect Ratio	 4:3 Native Aspect Ratio
Image size (diagonal)	 40" to greater than 300"/1.0 m to greater than 7.5 m
Projection Methods	Front, rear and ceiling
Projector Audio	2.0-watt stereo
Projector Interface	Interactive LCD Display or Menu system
Projector Interface Languages	 English, Spanish, French, German, Japanese, Korean, Portuguese, Italian, Norwegian, Russian, Chinese Simple, Chinese Traditional
Projector Control	 Menu, Keypad, ProjectorManager[™], RS-232
Mouse Control	• USB
Lamp	 170 W UHP / 2000 hours*
Dimensions	• 4.1" (H) x 10.3" (L) x 11.6" (W) 10.3 cm x 26.0 cm x 29.4 cm
Weight	• 7.5 lbs / 3.4 kg
Power Consumption	• 260 watts
Power Supply	• 85V – 240V at 50 – 60 Hz
Operating Temperature	• 10° – 35° C at sea level (0' – 10,000'); 50° – 95° F
Audible Noise	• 34dB
Approvals	 FCC A (US/Canada), UL & cUL (US/Canada), GOST (Russia), TUV GS (Germany), CCC (China), IRAM (Argentina), NOM (Mexico), MIC (Korea), C-Tick (Australia)
Lamp Warranty	90 days or 500 hours, whichever comes first
Product Warranty	2 years parts and labor
Accessory Warranty	• 1 year
	ed on the ambient environment. Conditions that may affect lamp

Actual lamp life may vary based on the ambient environment. Conditions that may affect lamp life include temperature, altitude, rapidly switching the projector on and off, and switching between standard and low power modes.

SHIPS STANDARD WITH:

- Soft Carry Case
- Navigator Remote
- Color coded cable straps
- M1-A Computer cable with USB Mouse
- 3.5mm computer audio cable
- RCA audio/video cable
- Power cord
- User manual, quick start card and CD

Optional Accessories

HW-PRESENTER Presenter Remote **HW-PRESENTER-RF** Presenter RF Remote Conductor Plus Remote **HW-CONDUCTOR+** LP-LITESHOW Liteshow® Wireless Connection SP-DVI-D Digital Computer Cable SP-M1-ADPT M1 to Component Adapter SW-PN2-1CD ProjectorNet[™] Software CA-ATA-019 ATA Roller Case CA-C230 Organizer Soft Case SP-CEIL-011 Ceiling Mount Kit SP-LOCK-B PC Guardian Projector Cable Lock A650 50"/127 cm Portable Projection Screen **HW-DLXSCRN** 60"/152 cm Deluxe Insta-Theatre Screen HW-WALLSCR84 80"/213 cm Pull-Down Screen SP-LAMP-017 Replacement Lamp

SERIOUS COMMITMENT

ASK Proxima's dedication to quality and customer satisfaction is reflected in service options that will bring you a greater return on your investment. ASK Proxima projectors come with a standard two-year limited factory warranty, including parts and labor and a 90-day lamp replacement. Our customer support offers you premium service and convenience, whatever your needs.

For service program details in your region, please visit:

www.askproxima.com



www.askproxima.com

InFocus Corporate Headquarters: 27700B SW Parkway Avenue Wilsonville, Oregon 97070-9215, USA • Phone: 503-685-8888 1-800-294-6400 • Fax: 503-685-8887

In Europe: InFocus International BV • Strawinskylaan 585 • 1077 XX Amsterdam
The Netherlands • Phone: (31) 20 5792000 • Fax: (31) 20 5792999
Freephone: 008000 4636287 (008000 INFOCUS)

InFocus Norge AS • K.G. Meldahlsvei 9 • Postboks 1403 • 1602 Fredrikstad • Norway Tel.: +47 69 38 11 00 • Fax.: +47 69 34 06 32 • Firmapost@infocus.com

In Asia: 238A Thomson Road • #18-01/04 Novena Square Singapore 307684 • Telephone: (65) 6334-9005 • Fax: (65) 6333-4525

[†] InFocus Corporation reserves the right to alter product offerings and specifications at any time without notice.